

X1100

Engine MTU , 16V2000G65F
Alternator LEROY SOMER , LSA502S4

STANDARD FEATURES

- Electronic governor
- Mechanically welded chassis with antivibration suspension
- Radiator for wiring temperature of 46°C max with mechanic fan
- Exhaust compensators with flanges
- 24 V charge alternator and starter
- Delivered with oil and coolant -30°C
- Manual for use and installation



Voltage	Power ESP kWe/kVA	Power PRP kWe/kVA	Standby Amps	Dimensions	Weight
415/240	880 / 1100	800 / 1000	1530		
400/230	880 / 1100	800 / 1000	1588	Leng : N/Amm [N/Ain]	N/Akg [N/Albs] Net
380/220	880 / 1100	800 / 1000	1671	Widt : N/Amm [N/Ain] Heig : N/Amm [N/Ain]	N/Akg [N/Albs] Gross





POWER DEFINITION

PRP : Prime Power is available for an unlimited number of annual operating hours in variable load applications, in accordance with ISO 8528-1.

ESP : The standby power rating is applicable for supplying emergency power in variable load applications in accordance with ISO 8528-1. Overload is not allowed.

TERM OF USE

Standard reference conditions ESP/PRP 27 C°/40 C° Air Intlet Temp, 1000 m/1000 m m A.S.L. 60 % relative humidity.

	Model	dB(A)@1m	dB(A)@7m	Dimensions	Weight	Tank
	ISO20	89	79	Leng : 6058mm [239in] Widt : 2438mm [96in] Heig : 2896mm [114in]	11596kg [25565lbs] 12341kg [27207lbs]	500 L
	CIR20SSi	85	75	Leng : 6058mm [239in] Widt : 2438mm [96in] Heig : 2896mm [114in]	14094kg [31072lbs] 14632kg [32258lbs]	500 L
	CIR20SSi-R	85	75	Leng : 6058mm [239in] Widt : 2438mm [96in] Heig : 2896mm [114in]	14084kg [31050lbs] 16244kg [35812lbs]	2000 L
	ISO20	89	79	Leng : 6058mm [239in] Widt : 2438mm [96in] Heig : 2896mm [114in]	11596kg [25565lbs] 12341kg [27207lbs]	500 L

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this CD Rom without notice, in a constant effort to improve the quality of its products.

SDMO Industries – 12bis rue de la Villeneuve – CS 92848 – 29 228 BREST CEDEX 2

Tel +33 (0)2 98 41 41 41 – Fax : +33 (0)2 98 41 63 07 – www.sdmo.com



ENGINE SPECIFICATIONS

DATA GENERAL DATA	Motor model	MTU 16V2000G65F , 4-temps, TURBO , AIR/AIR 16 X
	Cylinder arrangement	V
	Displacement (C.l.)	31.86
	Bore (mm) X Stroke (mm)	130 X 150
	Compression ratio	16
	Speed (RPM)	1500
	Pistons speed (m/s)	7.5
	Maximum stand-by power at rated RPM (kW)	975
	Frequency regulation (%)	N/A
	BMEP (bar)	22.35
	Governor type	Electronique
EXHAUST SYSTEM	Exhaust gas temperature (°F)	530
	Exhaust gas flow (L/s)	2950
	Max. exhaust back pressure (mm CE)	300
FUEL SYSTEM	Consumption @ 110% load (L/h)	228
	Consumption @ 100% load (L/h)	205
	Consumption @ 75% load (L/h)	152
	Consumption @ 50% load (L/h)	104
	Maximum fuel pump flow (L/hr)	600
OIL	Oil capacity (L)	102
	Min. oil pressure (bar)	4.7
	Max. oil pressure (bar)	7.5
	Oil consumption 100% load (L/h)	2.05
	Carter oil capacity (L)	92
THERMAL BALANCE	Heat rejection to exhaust (kW)	N/A
	Radiated heat to ambient (kW)	45
	Heat rejection to coolant (kW)	400
AIR INTAKE	AIR INTAKE_entree_max%	150
	Intake air flow (L/s)	1100
COOLANT SYSTEM	Radiator & Engine capacity (L)	N/A
	Max water temperature (°C)	102
	Outlet water temperature (°C)	95
	Fan power (kW)	41
	Fan air flow w/o restriction (m3/s)	21.3
	Available restriction on air flow (mm CE)	20
	Type of coolant	N/A
	Thermostat (°C)	N/A
EMISSIONS	Emissions PM (g/kW.h)	N/A
	Emission CO (g/kW.h)	N/A
	Emissions HCNOx (g/kWh)	N/A
	Emission HC (g/kW.h)	N/A

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this CD Rom without notice, in a constant effort to improve the quality of its products.

SDMO Industries – 12bis rue de la Villeneuve – CS 92848 – 29 228 BREST CEDEX 2

Tel +33 (0)2 98 41 41 41 – Fax : +33 (0)2 98 41 63 07 – www.sdmo.com



ALTERNATOR SPECIFICATIONS

DATA GENERAL DATA	Alternator brand	LEROY SOMER
	Alternator	LSA502S4
	Number of phase	3
	Power factor (Cos Phi)	0.8
	Altitude (m)	<1000
	Overspeed (rpm)	2250
	Number of pole	4
	Excitation system	AREP
	Insulation class / Temperature class	H / H
	Regulation	R448V50
	Total harmonics TGH/THC	<3.5
	Wave form : NEMA=TIF-TGH/THC	<50
	Wave form : CEI=FHT-TGH/THC	<2
	Number of bearing	1
	Coupling	DIRECT
	Voltage regulation 0 à 100%	0.5
	Recovery time (Delta U = 20% transitoire) (ms)	500
OTHER DATA	Continuous Nominal Rating 40°C (kVA)	1040
	Standby Rating 27°C (kVA)	1145
	Efficiencies 4/4 load (%)	94.7
	Air flow (m3/s)	1.8
	Short circuit ratio (Kcc)	0.3
	Direct axis synchro reactance unsaturated (Xd) (%)	394
	Quadra axis synchro reactance unsaturated (Xq) (%)	236
	Open circuit time constant (T'do) (ms)	3411
	Direct axis transient reactance saturated (X'd) (%)	20.8
	Short circuit transient time constant (T'd) (ms)	180
	Direct axis subtransient reactance saturated (X''d) (%)	17.6
	Subtransient time constant (T''d) (ms)	18
	Quadra axis subtransient reactance saturated (X''q) (%)	18.6
	Zero sequence reactance unsaturated (Xo) (%)	3.7
	Negative sequence reactance saturated (X2) (%)	18.2
	Armature time constant (Ta) (ms)	27
	No load excitation current (io) (ms)	0.9
	Full load excitation current (ic) (A)	4
	Full load excitation voltage (uc) (A)	44
	Recovery time (Delta U = 20% transitoire) (ms)	500
	Motor start (Delta U = 20% perm. or 50% trans.) (ms)	2383
	Transient dip (4/4 charge) - PF : 0,8 AR (%)	14.2
	No load losses (kW)	12.8
Heat rejection (kW)	45.8	

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this CD Rom without notice, in a constant effort to improve the quality of its products.

SDMO Industries – 12bis rue de la Villeneuve – CS 92848 – 29 228 BREST CEDEX 2

Tel +33 (0)2 98 41 41 41 – Fax : +33 (0)2 98 41 63 07 – www.sdmo.com

CONTROL PANEL

Standard

M80



M80

Specifications : Tachometer, Emergency stop button, client connection terminal strip, EC certified
 Engine parameters : Hours counter, Oil pressure gauge, Water temperature indicator, Oil pressure indicator

Option

TELYS

TELYS



Specifications : Frequency meter, Ammeter, Voltmeter
 Alarms and faults : Oil pressure, water temperature, No start-up, Overspeed, Min/max alternator, Min/max battery voltage, Low fuel level, Emergency stop
 Engine parameters : Hours counter, Oil pressure, Water temperature, Engine speed, Battery voltage, Fuel level

Option

KERYS

KERYS



Specifications : Frequency meter, Ammeter, Voltmeter
 Alarms and faults : Oil pressure, water temperature, No start-up, Overspeed, Min/max alternator, Min/max battery voltage, Low fuel level, Emergency stop
 Engine parameters : Hours counter, Oil pressure, Water temperature, Engine speed, Battery voltage, Fuel level
 Additional specifications : Website, Troubleshooting, Assistance and Maintenance, Plotting and logging, Load impact, 8 configurations available, Compliance with international standards...