

X1400

Engine MTU , 12V4000G21F
Alternator LEROY SOMER , LSA502L7

STANDARD FEATURES

- Electronic governor
- Mechanically welded chassis with antivibration suspension
- Radiator for wiring temperature of 46°C max with mechanic fan
- Exhaust compensators with flanges
- 24 V charge alternator and starter
- Delivered with oil and coolant -30°C
- Manual for use and installation



Voltage	Power ESP kWe/kVA	Power PRP kWe/kVA	Standby Amps	Dimensions	Weight
415/240	1120 / 1400	1018 / 1273	1948		
400/230	1120 / 1400	1018 / 1273	2021	Leng : 3870mm [152in]	9442kg [20816lbs] Net
380/220	1120 / 1400	1018 / 1273	2127	Widt : 1835mm [72in] Heig : 2210mm [87in]	9876kg [21773lbs] Gross






POWER DEFINITION

PRP : Prime Power is available for an unlimited number of annual operating hours in variable load applications, in accordance with ISO 8528-1.

ESP : The standby power rating is applicable for supplying emergency power in variable load applications in accordance with ISO 8528-1. Overload is not allowed.

TERM OF USE

Standard reference conditions ESP/PRP 27 C°/40 C° Air Inlet Temp, 1000 m/1000 m m A.S.L. 60 % relative humidity.

	Model	dB(A)@1m	dB(A)@7m	Dimensions	Weight	Tank
	CIR20SSi	84	74	Leng : 6058mm [239in] Widt : 2438mm [96in] Heig : 2896mm [114in]	16415kg [36189lbs] 17520kg [38625lbs]	500 L
	CIR20SSi-R	84	74	Leng : 6058mm [239in] Widt : 2438mm [96in] Heig : 2896mm [114in]	16868kg [37188lbs] 19365kg [42693lbs]	2000 L
	EUR40Si	85	75	Leng : 12192mm [480in] Widt : 2438mm [96in] Heig : 2896mm [114in]	21361kg [47093lbs] 22711kg [50069lbs]	500 L
	EUR40SSi	79	69	Leng : 12192mm [480in] Widt : 2438mm [96in] Heig : 2896mm [114in]	22561kg [49738lbs] 23910kg [52713lbs]	500 L
	ISO40	88	78	Leng : 12192mm [480in] Widt : 2438mm [96in] Heig : 2896mm [114in]	19022kg [41936lbs] 19681kg [43389lbs]	500 L

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this CD Rom without notice, in a constant effort to improve the quality of its products.

SDMO Industries – 12bis rue de la Villeneuve – CS 92848 – 29 228 BREST CEDEX 2

Tel +33 (0)2 98 41 41 41 – Fax : +33 (0)2 98 41 63 07 – www.sdmo.com



ENGINE SPECIFICATIONS

DATA GENERAL DATA	Motor model	MTU 12V4000G21F , 4-temps, TURBO , AIR/WATER 12 X
	Cylinder arrangement	V
	Displacement (C.l.)	48.75
	Bore (mm) X Stroke (mm)	165 X 190
	Compression ratio	16.6 : 1
	Speed (RPM)	1500
	Pistons speed (m/s)	9.5
	Maximum stand-by power at rated RPM (kW)	1330
	Frequency regulation (%)	0.5
	BMEP (bar)	19.77
	Governor type	ELEC
EXHAUST SYSTEM	Exhaust gas temperature (°F)	465
	Exhaust gas flow (L/s)	3500
	Max. exhaust back pressure (mm CE)	300
FUEL SYSTEM	Consumption @ 110% load (L/h)	302
	Consumption @ 100% load (L/h)	273
	Consumption @ 75% load (L/h)	206
	Consumption @ 50% load (L/h)	141
	Maximum fuel pump flow (L/hr)	1062
OIL	Oil capacity (L)	260
	Min. oil pressure (bar)	3
	Max. oil pressure (bar)	5.5
	Oil consumption 100% load (L/h)	1.48
	Carter oil capacity (L)	200
THERMAL BALANCE	Heat rejection to exhaust (kW)	731
	Radiated heat to ambient (kW)	90
	Heat rejection to coolant (kW)	515+240
AIR INTAKE	AIR INTAKE_entree_max%	150
	Intake air flow (L/s)	1600
COOLANT SYSTEM	Radiator & Engine capacity (L)	N/A
	Max water temperature (°C)	97
	Outlet water temperature (°C)	93
	Fan power (kW)	N/A
	Fan air flow w/o restriction (m3/s)	20.1
	Available restriction on air flow (mm CE)	21
	Type of coolant	COOLELF-MDX
	Thermostat (°C)	79/--
EMISSIONS	Emissions PM (g/kW.h)	N/A
	Emission CO (g/kW.h)	N/A
	Emissions HCNOx (g/kWh)	N/A
	Emission HC (g/kW.h)	N/A

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this CD Rom without notice, in a constant effort to improve the quality of its products.

SDMO Industries – 12bis rue de la Villeneuve – CS 92848 – 29 228 BREST CEDEX 2

Tel +33 (0)2 98 41 41 41 – Fax : +33 (0)2 98 41 63 07 – www.sdmo.com



ALTERNATOR SPECIFICATIONS

DATA GENERAL DATA	Alternator brand	LEROY SOMER
	Alternator	LSA502L7
	Number of phase	3
	Power factor (Cos Phi)	0.8
	Altitude (m)	<1000
	Overspeed (rpm)	2250
	Number of pole	4
	Excitation system	AREP
	Insulation class / Temperature class	H / H
	Regulation	R448V50
	Total harmonics TGH/THC	<3.5
	Wave form : NEMA=TIF-TGH/THC	<50
	Wave form : CEI=FHT-TGH/THC	<2
	Number of bearing	1
	Coupling	DIRECT
	Voltage regulation 0 à 100%	0.5
	Recovery time (Delta U = 20% transitoire) (ms)	500
OTHER DATA	Continuous Nominal Rating 40°C (kVA)	1350
	Standby Rating 27°C (kVA)	1485
	Efficiencies 4/4 load (%)	95.3
	Air flow (m3/s)	1.8
	Short circuit ratio (Kcc)	0.34
	Direct axis synchro reactance unsaturated (Xd) (%)	364
	Quadra axis synchro reactance unsaturated (Xq) (%)	218
	Open circuit time constant (T'do) (ms)	3750
	Direct axis transient reactance saturated (X'd) (%)	17.4
	Short circuit transient time constant (T'd) (ms)	180
	Direct axis subtransient reactance saturated (X''d) (%)	14.8
	Subtransient time constant (T''d) (ms)	18
	Quadra axis subtransient reactance saturated (X''q) (%)	15.5
	Zero sequence reactance unsaturated (Xo) (%)	3.6
	Negative sequence reactance saturated (X2) (%)	15.2
	Armature time constant (Ta) (ms)	27
	No load excitation current (io) (ms)	1
	Full load excitation current (ic) (A)	4
	Full load excitation voltage (uc) (A)	44
	Recovery time (Delta U = 20% transitoire) (ms)	500
	Motor start (Delta U = 20% perm. or 50% trans.) (ms)	3181
	Transient dip (4/4 charge) - PF : 0,8 AR (%)	12.4
	No load losses (kW)	15.26
Heat rejection (kW)	53.26	

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this CD Rom without notice, in a constant effort to improve the quality of its products.

SDMO Industries – 12bis rue de la Villeneuve – CS 92848 – 29 228 BREST CEDEX 2

Tel +33 (0)2 98 41 41 41 – Fax : +33 (0)2 98 41 63 07 – www.sdmo.com

CONTROL PANEL

Standard

M80



M80

Specifications : Tachometer, Emergency stop button, client connection terminal strip, EC certified
 Engine parameters : Hours counter, Oil pressure gauge, Water temperature indicator, Oil pressure indicator

Option

TELYS



TELYS

Specifications : Frequency meter, Ammeter, Voltmeter
 Alarms and faults : Oil pressure, water temperature, No start-up, Overspeed, Min/max alternator, Min/max battery voltage, Low fuel level, Emergency stop
 Engine parameters : Hours counter, Oil pressure, Water temperature, Engine speed, Battery voltage, Fuel level

Option

KERYS



KERYS

Specifications : Frequency meter, Ammeter, Voltmeter
 Alarms and faults : Oil pressure, water temperature, No start-up, Overspeed, Min/max alternator, Min/max battery voltage, Low fuel level, Emergency stop
 Engine parameters : Hours counter, Oil pressure, Water temperature, Engine speed, Battery voltage, Fuel level
 Additional specifications : Website, Troubleshooting, Assistance and Maintenance, Plotting and logging, Load impact, 8 configurations available, Compliance with international standards...