



X2800

Engine MTU , 20V4000G23F
Alternator LEROY SOMER , LSA53S75

STANDARD FEATURES

- Electronic governor
- Mechanically welded chassis with antivibration suspension
- Air cooler for wiring temperature of 47/50°C with electric fan
- Exhaust compensators with flanges
- 24 V charge alternator and starter
- Delivered with oil
- Manual for use and installation



Voltage	Power ESP kWe/kVA	Power PRP kWe/kVA	Standby Amps	Dimensions	Weight
415/240	2240 / 2800	2036 / 2545	3895		
400/230	2240 / 2800	2036 / 2545	4042	Leng : 5730mm [226in]	17290kg [38118lbs] Net
380/220	2240 / 2800	2036 / 2545	4254	Widt : 2250mm [89in]	17901kg [39465lbs] Gross
				Heig : 2454mm [97in]	

POWER DEFINITION

PRP : Prime Power is available for an unlimited number of annual operating hours in variable load applications, in accordance with ISO 8528-1.

ESP : The standby power rating is applicable for supplying emergency power in variable load applications in accordance with ISO 8528-1. Overload is not allowed.

TERM OF USE

Standard reference conditions ESP/PRP 27 C°/40 C° Air Intlet Temp, 1000 m/1000 m m A.S.L. 60 % relative humidity.

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this CD Rom without notice, in a constant effort to improve the quality of its products.

SDMO Industries – 12bis rue de la Villeneuve – CS 92848 – 29 228 BREST CEDEX 2

Tel +33 (0)2 98 41 41 41 – Fax : +33 (0)2 98 41 63 07 – www.sdmo.com



ENGINE SPECIFICATIONS

DATA GENERAL DATA	Motor model	MTU 20V4000G23F , 4-temps, TURBO , AIR/WATER 20 X
	Cylinder arrangement	V
	Displacement (C.l.)	95.33
	Bore (mm) X Stroke (mm)	170 X 210
	Compression ratio	16.5
	Speed (RPM)	1500
	Pistons speed (m/s)	10.5
	Maximum stand-by power at rated RPM (kW)	2420
	Frequency regulation (%)	0.5
	BMEP (bar)	18.46
	Governor type	ELEC
EXHAUST SYSTEM	Exhaust gas temperature (°F)	500
	Exhaust gas flow (L/s)	6800
	Max. exhaust back pressure (mm CE)	300
FUEL SYSTEM	Consumption @ 110% load (L/h)	543
	Consumption @ 100% load (L/h)	499
	Consumption @ 75% load (L/h)	386
	Consumption @ 50% load (L/h)	272
	Maximum fuel pump flow (L/hr)	1500
OIL	Oil capacity (L)	300
	Min. oil pressure (bar)	4.9
	Max. oil pressure (bar)	7.7
	Oil consumption 100% load (L/h)	1.5
	Carter oil capacity (L)	240
THERMAL BALANCE	Heat rejection to exhaust (kW)	N/A
	Radiated heat to ambient (kW)	105
	Haet rejection to coolant (kW)	870/300
AIR INTAKE	AIR INTAKE_entree_max%	150
	Intake air flow (L/s)	2600
COOLANT SYSTEM	Radiator & Engine capacity (L)	N/A
	Max water temperature (°C)	104
	Outlet water temperature (°C)	100
	Fan power (kW)	N/A
	Fan air flow w/o restriction (m3/s)	N/A
	Available restriction on air flow (mm CE)	N/A
	Type of coolant	COOLELF-MDX
	Thermostat (°C)	79/92
EMISSIONS	Emissions PM (g/kW.h)	N/A
	Emission CO (g/kW.h)	N/A
	Emissions HCNOx (g/kWh)	N/A
	Emission HC (g/kW.h)	N/A

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this CD Rom without notice, in a constant effort to improve the quality of its products.

SDMO Industries – 12bis rue de la Villeneuve – CS 92848 – 29 228 BREST CEDEX 2

Tel +33 (0)2 98 41 41 41 – Fax : +33 (0)2 98 41 63 07 – www.sdmo.com



ALTERNATOR SPECIFICATIONS

DATA GENERAL DATA	Alternator brand	LEROY SOMER
	Alternator	LSA53S75
	Number of phase	3
	Power factor (Cos Phi)	0.8
	Altitude (m)	1000
	Overspeed (rpm)	2160
	Number of pole	4
	Excitation system	AREP
	Insulation class / Temperature class	H / H
	Regulation	R449
	Total harmonics TGH/THC	<2.5
	Wave form : NEMA=TIF-TGH/THC	<50
	Wave form : CEI=FHT-TGH/THC	<2
	Number of bearing	1
	Coupling	DIRECT
	Voltage regulation 0 à 100%	0.5
	Recovery time (Delta U = 20% transitoire) (ms)	800
OTHER DATA	Continuous Nominal Rating 40°C (kVA)	2648
	Standby Rating 27°C (kVA)	2913
	Efficiencies 4/4 load (%)	96.3
	Air flow (m3/s)	2.8
	Short circuit ratio (Kcc)	0.46
	Direct axis synchro reactance unsaturated (Xd) (%)	274
	Quadra axis synchro reactance unsaturated (Xq) (%)	165
	Open circuit time constant (T'do) (ms)	2880
	Direct axis transient reactance saturated (X'd) (%)	22.1
	Short circuit transient time constant (T'd) (ms)	272
	Direct axis subtransient reactance saturated (X''d) (%)	12.1
	Subtransient time constant (T''d) (ms)	25
	Quadra axis subtransient reactance saturated (X''q) (%)	15
	Zero sequence reactance unsaturated (Xo) (%)	2.8
	Negative sequence reactance saturated (X2) (%)	13.6
	Armature time constant (Ta) (ms)	58
	No load excitation current (io) (ms)	1.3
	Full load excitation current (ic) (A)	4.8
	Full load excitation voltage (uc) (A)	52
	Recovery time (Delta U = 20% transitoire) (ms)	800
	Motor start (Delta U = 20% perm. or 50% trans.) (ms)	5600
	Transient dip (4/4 charge) - PF : 0,8 AR (%)	12
No load losses (kW)	28	
Heat rejection (kW)	81.5	

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this CD Rom without notice, in a constant effort to improve the quality of its products.

SDMO Industries – 12bis rue de la Villeneuve – CS 92848 – 29 228 BREST CEDEX 2

Tel +33 (0)2 98 41 41 41 – Fax : +33 (0)2 98 41 63 07 – www.sdmo.com

CONTROL PANEL

Standard

M80



M80

Specifications : Tachometer, Emergency stop button, client connection terminal strip, EC certified
 Engine parameters : Hours counter, Oil pressure gauge, Water temperature indicator, Oil pressure indicator

Option

TELYS



TELYS

Specifications : Frequency meter, Ammeter, Voltmeter
 Alarms and faults : Oil pressure, water temperature, No start-up, Overspeed, Min/max alternator, Min/max battery voltage, Low fuel level, Emergency stop
 Engine parameters : Hours counter, Oil pressure, Water temperature, Engine speed, Battery voltage, Fuel level

Option

KERYS



KERYS

Specifications : Frequency meter, Ammeter, Voltmeter
 Alarms and faults : Oil pressure, water temperature, No start-up, Overspeed, Min/max alternator, Min/max battery voltage, Low fuel level, Emergency stop
 Engine parameters : Hours counter, Oil pressure, Water temperature, Engine speed, Battery voltage, Fuel level
 Additional specifications : Website, Troubleshooting, Assistance and Maintenance, Plotting and logging, Load impact, 8 configurations available, Compliance with international standards...