

J130K

Engine JOHN DEERE , 6068TF220
Alternator LEROY SOMER , LSA442S7

STANDARD FEATURES

- Mechanic governor
- Mechanically welded chassis with antivibration suspension
- Main line circuit breaker
- Radiator for wiring temperature of 48/50°C max with mechanical fan
- Protective grille for fan and rotating parts
- 9 dB(A) silencer supplied separately
- Charger DC starting battery with electrolyte
- 12 V charge alternator and starter
- Delivered with oil and coolant -30°C
- Manual for use and installation



Voltage	Power ESP kWe/kVA	Power PRP kWe/kVA	Standby Amps	Dimensions	Weight
415/240	106 / 132	96 / 120	184		
400/230	106 / 132	96 / 120	191	Leng : 2370mm [93in]	1570kg [3461lbs] Net
380/220	106 / 132	96 / 120	201	Widt : 1114mm [44in]	1910kg [4211lbs] Gross
240 TRI	106 / 132	96 / 120	318	Heig : 1480mm [58in]	
230 TRI	106 / 132	96 / 120	331		
220 TRI	106 / 132	96 / 120	346		
220/127	106 / 132	96 / 120	346		
200/115	106 / 132	96 / 120	381		



POWER DEFINITION

PRP : Prime Power is available for an unlimited number of annual operating hours in variable load applications, in accordance with ISO 8528-1.

ESP : The standby power rating is applicable for supplying emergency power in variable load applications in accordance with ISO 8528-1. Overload is not allowed.

TERM OF USE

Standard reference conditions ESP/PRP 25 C°/25 C° Air Intlet Temp, 1000 m/1000 m m A.S.L. 60 % relative humidity.

	Model	dB(A)@1m	dB(A)@7m	Dimensions	Weight	Tank
	M226-DW	77.6	67.6	Leng : 3560mm [140in] Widt : 1200mm [47in] Heig : 2182mm [86in]	2560kg [5644lbs] 3443kg [7591lbs]	868 L
	M226	77.6	67.6	Leng : 3508mm [138in] Widt : 1200mm [47in] Heig : 1830mm [72in]	2160kg [4762lbs] 2500kg [5512lbs]	340 L



ENGINE SPECIFICATIONS

DATA GENERAL DATA	Motor model	JOHN DEERE 6068TF220 , 4-temps, TURBO , N/A 6 X
	Cylinder arrangement	L
	Displacement (C.l.)	6.72
	Bore (mm) X Stroke (mm)	106 X 127
	Compression ratio	17 : 1
	Speed (RPM)	1500
	Pistons speed (m/s)	6.35
	Maximum stand-by power at rated RPM (kW)	117
	Frequency regulation (%)	2.5
	BMEP (bar)	12.61
	Governor type	MECA
EXHAUST SYSTEM	Exhaust gas temperature (°F)	561
	Exhaust gas flow (L/s)	290
	Max. exhaust back pressure (mm CE)	750
FUEL SYSTEM	Consumption @ 110% load (L/h)	29
	Consumption @ 100% load (L/h)	26
	Consumption @ 75% load (L/h)	18.5
	Consumption @ 50% load (L/h)	13.5
	Maximum fuel pump flow (L/hr)	108
OIL	Oil capacity (L)	21.5
	Min. oil pressure (bar)	1
	Max. oil pressure (bar)	5
	Oil consumption 100% load (L/h)	0.029
	Carter oil capacity (L)	20.6
THERMAL BALANCE	Heat rejection to exhaust (kW)	94
	Radiated heat to ambient (kW)	14
	Haet rejection to coolant (kW)	65
AIR INTAKE	AIR INTAKE_entree_max%	625
	Intake air flow (L/s)	135
COOLANT SYSTEM	Radiator & Engine capacity (L)	27.3
	Max water temperature (°C)	105
	Outlet water temperature (°C)	93
	Fan power (kW)	3
	Fan air flow w/o restriction (m3/s)	4.4
	Available restriction on air flow (mm CE)	20
	Type of coolant	GENCOOL
	Thermostat (°C)	82-94
EMISSIONS	Emissions PM (g/kW.h)	N/A
	Emission CO (g/kW.h)	N/A
	Emissions HCNOx (g/kWh)	N/A
	Emission HC (g/kW.h)	N/A

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this CD Rom without notice, in a constant effort to improve the quality of its products.

SDMO Industries – 12bis rue de la Villeneuve – CS 92848 – 29 228 BREST CEDEX 2

Tel +33 (0)2 98 41 41 41 – Fax : +33 (0)2 98 41 63 07 – www.sdmo.com



ALTERNATOR SPECIFICATIONS

DATA GENERAL DATA	Alternator brand	LEROY SOMER
	Alternator	LSA442S7
	Number of phase	3
	Power factor (Cos Phi)	0.8
	Altitude (m)	<1000
	Overspeed (rpm)	2250
	Number of pole	4
	Excitation system	SHUNT
	Insulation class / Temperature class	H / H
	Regulation	R230
	Total harmonics TGH/THC	<2
	Wave form : NEMA=TIF-TGH/THC	<50
	Wave form : CEI=FHT-TGH/THC	<2
	Number of bearing	1
	Coupling	DIRECT
	Voltage regulation 0 à 100%	0.5
	Recovery time (Delta U = 20% transitoire) (ms)	500
OTHER DATA	Continuous Nominal Rating 40°C (kVA)	125
	Standby Rating 27°C (kVA)	138
	Efficiencies 4/4 load (%)	91.6
	Air flow (m3/s)	0.37
	Short circuit ratio (Kcc)	0.33
	Direct axis synchro reactance unsaturated (Xd) (%)	363
	Quadra axis synchro reactance unsaturated (Xq) (%)	218
	Open circuit time constant (T'do) (ms)	2734
	Direct axis transient reactance saturated (X'd) (%)	13.2
	Short circuit transient time constant (T'd) (ms)	100
	Direct axis subtransient reactance saturated (X''d) (%)	7.9
	Subtransient time constant (T''d) (ms)	10
	Quadra axis subtransient reactance saturated (X''q) (%)	9.6
	Zero sequence reactance unsaturated (Xo) (%)	0.7
	Negative sequence reactance saturated (X2) (%)	8.8
	Armature time constant (Ta) (ms)	15
	No load excitation current (io) (ms)	0.5
	Full load excitation current (ic) (A)	2
	Full load excitation voltage (uc) (A)	36
	Recovery time (Delta U = 20% transitoire) (ms)	500
	Motor start (Delta U = 20% perm. or 50% trans.) (ms)	244
	Transient dip (4/4 charge) - PF : 0,8 AR (%)	16.6
	No load losses (kW)	1.97
Heat rejection (kW)	9.41	

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this CD Rom without notice, in a constant effort to improve the quality of its products.

SDMO Industries – 12bis rue de la Villeneuve – CS 92848 – 29 228 BREST CEDEX 2

Tel +33 (0)2 98 41 41 41 – Fax : +33 (0)2 98 41 63 07 – www.sdmo.com

CONTROL PANEL

Standard

NEXYS



NEXYS

Specifications : Frequency meter, Ammeter, Voltmeter
Alarms and faults : Oil pressure, water temperature, Overcrank, Overspeed (>60 kVA), Min/max alternator, Low fuel level, Emergency stop
Engine parameters : Hours counter, Engine speed, Battery voltage, Fuel level, Air preheating

Option

TELYS



TELYS

Specifications : Frequency meter, Ammeter, Voltmeter
Alarms and faults : Oil pressure, water temperature, No start-up, Overspeed, Min/max alternator, Min/max battery voltage, Low fuel level, Emergency stop
Engine parameters : Hours counter, Oil pressure, Water temperature, Engine speed, Battery voltage, Fuel level