



T9HK

Engine MITSUBISHI , L2E-SDH
Alternator SOGA , FT2MBS

STANDARD FEATURES

- Mechanic governor
- Mechanically welded chassis with antivibration suspension
- Main line circuit breaker
- Radiator for wiring temperature of 48/50°C max with mechanical fan
- Protective grille for fan and rotating parts
- 9 dB(A) silencer supplied separately
- Charger DC starting battery with electrolyte
- 12 V charge alternator and starter
- Delivered with oil and coolant -30°C
- Manual for use and installation



Voltage	Power ESP kWe/kVA	Power PRP kWe/kVA	Standby Amps	Dimensions	Weight
400/230	7.2 / 9	- / -	13	Leng : 1220mm [48in] Widt : 700mm [28in] Heig : 922mm [36in]	240kg [529lbs] Net 290kg [639lbs] Gross

POWER DEFINITION

PRP : Prime Power is available for an unlimited number of annual operating hours in variable load applications, in accordance with ISO 8528-1.

ESP : The standby power rating is applicable for supplying emergency power in variable load applications in accordance with ISO 8528-1. Overload is not allowed.

TERM OF USE

Standard reference conditions ESP/PRP 25 C°/NA Air Intlet Temp, 100 m/NA m A.S.L. 60 % relative humidity.

Model	dB(A)@1m	dB(A)@7m	Dimensions	Weight	Tank
M125	78	68	Leng : 1482mm [58in] Widt : 760mm [30in] Heig : 1030mm [41in]	360kg [794lbs] 410kg [904lbs]	50 L



This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this CD Rom without notice, in a constant effort to improve the quality of its products.

SDMO Industries – 12bis rue de la Villeneuve – CS 92848 – 29 228 BREST CEDEX 2

Tel +33 (0)2 98 41 41 41 – Fax : +33 (0)2 98 41 63 07 – www.sdmo.com



ENGINE SPECIFICATIONS

DATA GENERAL DATA	Motor model	MITSUBISHI L2E-SDH , 4-temps, ATHMO , N/A 2
		X
	Cylinder arrangement	L
	Displacement (C.I.)	0.64
	Bore (mm) X Stroke (mm)	76 X 70
	Compression ratio	23 : 1
	Speed (RPM)	3000
	Pistons speed (m/s)	7
	Maximum stand-by power at rated RPM (kW)	9.68
	Frequency regulation (%)	2.5
	BMEP (bar)	5.54
	Governor type	MECA
EXHAUST SYSTEM	Exhaust gas temperature (°F)	560
	Exhaust gas flow (L/s)	34.8
	Max. exhaust back pressure (mm CE)	800
FUEL SYSTEM	Consumption @ 110% load (L/h)	N/A
	Consumption @ 100% load (L/h)	3.3
	Consumption @ 75% load (L/h)	2.6
	Consumption @ 50% load (L/h)	2.1
	Maximum fuel pump flow (L/hr)	18
OIL	Oil capacity (L)	2.4
	Min. oil pressure (bar)	0.5
	Max. oil pressure (bar)	4
	Oil consumption 100% load (L/h)	0.009
	Carter oil capacity (L)	N/A
THERMAL BALANCE	Heat rejection to exhaust (kW)	10
	Radiated heat to ambient (kW)	1
	Heat rejection to coolant (kW)	12.4
AIR INTAKE	AIR INTAKE_entree_max%	310
	Intake air flow (L/s)	13.2
COOLANT SYSTEM	Radiator & Engine capacity (L)	2.75
	Max water temperature (°C)	111
	Outlet water temperature (°C)	93
	Fan power (kW)	0.7
	Fan air flow w/o restriction (m3/s)	0.4
	Available restriction on air flow (mm CE)	7.5
	Type of coolant	GENCOOL
	Thermostat (°C)	76,5-90
EMISSIONS	Emissions PM (g/kW.h)	N/A
	Emission CO (g/kW.h)	N/A
	Emissions HCNOx (g/kWh)	N/A
	Emission HC (g/kW.h)	N/A

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this CD Rom without notice, in a constant effort to improve the quality of its products.

SDMO Industries – 12bis rue de la Villeneuve – CS 92848 – 29 228 BREST CEDEX 2

Tel +33 (0)2 98 41 41 41 – Fax : +33 (0)2 98 41 63 07 – www.sdmo.com



ALTERNATOR SPECIFICATIONS

DATA GENERAL DATA	Alternator brand	SOGA
	Alternator	FT2MBS
	Number of phase	3
	Power factor (Cos Phi)	0.8
	Altitude (m)	1000
	Overspeed (rpm)	N/A
	Number of pole	2
	Excitation system	N/A
	Insulation class / Temperature class	H / H
	Regulation	N/A
	Total harmonics TGH/THC	N/A
	Wave form : NEMA=TIF-TGH/THC	N/A
	Wave form : CEI=FHT-TGH/THC	N/A
	Number of bearing	1
	Coupling	DIRECT
	Voltage regulation 0 à 100%	N/A
	Recovery time (Delta U = 20% transitoire) (ms)	N/A
OTHER DATA	Continuous Nominal Rating 40°C (kVA)	16
	Standby Rating 27°C (kVA)	17.6
	Efficiencies 4/4 load (%)	85
	Air flow (m3/s)	N/A
	Short circuit ratio (Kcc)	0.6
	Direct axis synchro reactance unsaturated (Xd) (%)	N/A
	Quadra axis synchro reactance unsaturated (Xq) (%)	N/A
	Open circuit time constant (T'do) (ms)	N/A
	Direct axis transient reactance saturated (X'd) (%)	N/A
	Short circuit transient time constant (T'd) (ms)	N/A
	Direct axis subtransient reactance saturated (X''d) (%)	N/A
	Subtransient time constant (T''d) (ms)	N/A
	Quadra axis subtransient reactance saturated (X''q) (%)	N/A
	Zero sequence reactance unsaturated (Xo) (%)	N/A
	Negative sequence reactance saturated (X2) (%)	N/A
	Armature time constant (Ta) (ms)	N/A
	No load excitation current (io) (ms)	N/A
	Full load excitation current (ic) (A)	N/A
	Full load excitation voltage (uc) (A)	N/A
	Recovery time (Delta U = 20% transitoire) (ms)	N/A
	Motor start (Delta U = 20% perm. or 50% trans.) (ms)	N/A
	Transient dip (4/4 charge) - PF : 0,8 AR (%)	N/A
	No load losses (kW)	N/A
Heat rejection (kW)	N/A	

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this CD Rom without notice, in a constant effort to improve the quality of its products.

SDMO Industries – 12bis rue de la Villeneuve – CS 92848 – 29 228 BREST CEDEX 2

Tel +33 (0)2 98 41 41 41 – Fax : +33 (0)2 98 41 63 07 – www.sdmo.com

CONTROL PANEL

Standard

NEXYS



NEXYS

Specifications : Frequency meter, Ammeter, Voltmeter
Alarms and faults : Oil pressure, water temperature, Overcrank, Overspeed (>60 kVA), Min/max alternator, Low fuel level, Emergency stop
Engine parameters : Hours counter, Engine speed, Battery voltage, Fuel level, Air preheating

Option

TELYS



TELYS

Specifications : Frequency meter, Ammeter, Voltmeter
Alarms and faults : Oil pressure, water temperature, No start-up, Overspeed, Min/max alternator, Min/max battery voltage, Low fuel level, Emergency stop
Engine parameters : Hours counter, Oil pressure, Water temperature, Engine speed, Battery voltage, Fuel level